

Technical Specification | Audience 10

Sensitivity (2.83 V/1 m): 86 dB

Recommended Amp. Power: Small size rooms: >30 watts
 Medium size rooms: >70 watts
 Large size rooms: -- watts

IEC Long Term Power Handling: >150 watts

Impedance, Nominal: 4 ohms
 Impedance, (20 - 200 Hz): 3.8 - 12.3 ohms
 Impedance, (200 - 20 kHz): 4.0 - 22.9 ohms
 Impedance, Phase Shift (20 - 200 Hz): -32.8° - +29.1°
 Impedance, Phase Shift (200 - 20 kHz): -34.4° - +46.4°
 Impedance, HF (200 kHz): 6.9 ohms

Frequency Response (+/- 3 dB): 45 Hz - 22 kHz

Resonance Frequency: 46 Hz
 Internal Cabinet Volume: 13 litres
 Bass Principle: Bass reflex

Weight: 6.8 kg
 Dimensions (W x H x L): 230 x 315 x 297 mm

Crossover: 2 way.

Crossover Frequencies: 2500 Hz

Crossover Slope: Woofer: 6 dB/oct, Tweeter 12 dB/oct

Connection: Gold binding posts

Recommended Placing: Stand
 Wall - with port plugs
 Book shelf - with port plugs

Remarks: Tweeter: 28 mm soft dome.
 Magnetic fluid.
 4 mm die-cast aluminium front.
 Pure aluminium wire voice coil.
 Rear chamber.
 Woofer: 19 cm polypropylene cone.
 Powerful magnet system.
 Port plugs included.

DYNAUDIO International GmbH

Ohepark 2
 21224 Rosengarten
 Germany
 Phone +49 (0)4108 - 4180 - 0
 Fax +49 (0)4108 - 4180 - 10
 E-Mail info@dynaudio.de