

Technical Specification_Audience 42

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >25 watts
	Medium size rooms: >65 watts
	Large size rooms: -- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20-200 Hz):	3.8 - 11.4 ohms
Impedance, (200-20 kHz):	3.7 - 18.7 ohms
Impedance, Phase Shift (20-200 Hz):	-31.0° - +32.7°
Impedance, Phase Shift (200-20 kHz):	-16.2° - +45.5°
Impedance, HF (200 kHz):	16.8 ohms
Frequency Response (+/- 3 dB):	53 Hz - 28 kHz
Resonance Frequency:	61 Hz
Internal Cabinet Volume:	7 litres
Bass Principle:	Bass reflex
Weight:	4.8 kg
Dimensions (W x H x L):	170 x 282 x 246 mm
Crossover:	2 way.
	The crossover is impedance corrected
Crossover Frequencies:	1800 Hz
Crossover Slope:	Woofer 6 dB/oct; Tweeter 6 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Stand

Remarks: Tweeter: 28 mm soft dome.
Magnetic fluid.
Pure aluminium wire voice coil.
Rear chamber.

Woofer: 15 cm polypropylene cone.
75 mm pure aluminium wire voice coil.

Cabinet: Front baffle 19 mm MDF.
Port plugs included.

DYNAUDIO Vertriebs GmbH
Ohepark 2
21224 Rosengarten-Nenndorf
Telefon 04108 - 4180 - 0
Telefax 04108 - 4180 - 10
E-Mail d@dynaudio.de