

Technical Specification | Audience 60

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >25 watts
	Medium size rooms: >65 watts
	Large size rooms: -- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.5 - 11.9 ohms
Impedance, (200 - 20 kHz):	3.6 - 12.9 ohms
Impedance, Phase Shift (20 - 200 Hz):	-33.0° - +31.9°
Impedance, Phase Shift (200 - 20 kHz):	-20.1° - +36.7°
Impedance, HF (200 kHz):	7.8 ohms
Frequency Response (+/- 3 dB):	38 Hz - 25 kHz
Resonance Frequency:	43 Hz
Internal Cabinet Volume:	12 litres
Bass Principle:	Bass reflex
Weight:	13.5 kg
Dimensions (W x H x L):	204 x 799 x 256 mm
Crossover:	2 way.
	The crossover is impedance corrected
Crossover Frequencies:	2100 Hz
Crossover Slope:	Woofer: 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Floor
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofer: 17 cm polypropylene cone. 75 mm pure aluminium wire voice coil. Cabinet: Front baffle 28 mm MDF. Port plugs and spikes included.

DYNAUDIO International GmbH

Ohemark 2
 21224 Rosengarten
 Germany
 Phone +49 (0)4108 - 4180 - 0
 Fax +49 (0)4108 - 4180 - 10
 E-Mail info@dynaudio.de