

Technical Specification | Audience 7

Sensitivity (2.83 V/1 m):	87 dB
Recommended Amp. Power:	Small size rooms: >20 watts
	Medium size rooms: >50 watts
	Large size rooms: >100 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	4.3 - 9.1 ohms
Impedance, (200 - 20 kHz):	4.6 - 10.7 ohms
Impedance, Phase Shift (20 - 200 Hz):	-20.0° - +23.1°
Impedance, Phase Shift (200 - 20 kHz):	-18.6° - +27.8°
Impedance, HF (200 kHz):	7.0 ohms
Frequency Response (+/- 3 dB):	37 Hz - 28 kHz
Resonance Frequency:	34 Hz
Internal Cabinet Volume:	26 litres
Bass Principle:	Bass reflex
Weight:	11.5 kg
Dimensions (W x H x L):	271 x 436 x 338 mm
Crossover:	2 way.
	The crossover is impedance corrected
Crossover Frequencies:	2 kHz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter 12 dB/oct
Connection:	Gold binding posts
Recommended Placing:	Stand
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofer: 24 cm polypropylene cone. 75 mm pure aluminium wire voice coil. Port plugs included.

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de