

Technical Specification | Audience 8

Sensitivity (2.83 V/1 m):	87 dB
Recommended Amp. Power:	Small size rooms: >20 watts
	Medium size rooms: >50 watts
	Large size rooms: >100 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	4.1 - 9.1 ohms
Impedance, (200 - 20 kHz):	4.3 - 6.7 ohms
Impedance, Phase Shift (20 - 200 Hz):	-22.4° - +24.9°
Impedance, Phase Shift (200 - 20 kHz):	-4.8° - +12.8°
Impedance, HF (200 kHz):	6.5 ohms
Frequency Response (+/- 3 dB):	36 Hz - 24 kHz
Resonance Frequency:	33 Hz
Internal Cabinet Volume:	28 litres
Bass Principle:	Bass reflex
Weight:	16 kg
Dimensions (W x H x L):	204 x 899 x 257 mm
Crossover:	2 way.
Crossover Frequencies:	3.6 kHz
Crossover Slope:	Woofer: 6 dB/oct; Tweeter 12 dB/oct
Connection:	Gold binding posts
Recommended Placing:	Floor, free standing
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofer: 2 x 17 cm polypropylene cone. 75 mm pure aluminium wire voice coil. Port plugs and spikes included.

DYNAUDIO International GmbH

Ohepark 2
 21224 Rosengarten
 Germany
 Phone +49 (0)4108 - 4180 - 0
 Fax +49 (0)4108 - 4180 - 10
 E-Mail info@dynaudio.de