

Technical Specification | Audience 9

Sensitivity (2.83 V/1 m): 89 dB

Recommended Amp. Power: Medium size rooms: >30 watts
Large size rooms: >60 watts

IEC Long Term Power Handling: 200 watts

Impedance, Nominal: 4 ohms

Impedance, (20 - 200 Hz): 2.9 - 6.9 ohms

Impedance, (200 - 20 kHz): 3.9 - 5.2 ohms

Impedance, Phase Shift (20 - 200 Hz): -28.5° - +19.8°

Impedance, Phase Shift (200 - 20 kHz): -7.6° - +16.1°

Impedance, HF (200 kHz): 4.8 ohms

Frequency Response (+/- 3 dB): 36 Hz - 20 kHz

Resonance Frequency: 22 Hz

Internal Cabinet Volume: 61 litres

Bass Principle: Bass reflex

Weight: 28 kg

Dimensions (W x H x L): 271 x 1097 x 338 mm

Crossover: 3 way.
The crossover is impedance corrected

Crossover Frequencies: 600 Hz + 2700 Hz

Crossover Slope: Woofer: 12 dB/oct, Midrange: 6 dB/oct, Tweeter 12 dB/oct

Connection: Gold binding posts

Recommended Placing: Floor, free standing

Remarks: Tweeter: 28 mm soft dome.
Magnetic fluid.
4 mm die-cast aluminium front.
Pure aluminium wire voice coil.
Double magnet system.
Rear chamber.

Midrange: 15 cm with die cast basket.
38 mm pure aluminium wire voice coil.

Woofer: 24 cm polypropylene cone.
75 mm pure aluminium wire voice coil.

Port plugs and spikes included.

DYNAUDIO International GmbH

Ohepark 2

21224 Rosengarten

Germany

Phone +49 (0)4108 - 4180 - 0

Fax +49 (0)4108 - 4180 - 10

E-Mail info@dynaudio.de

USt-Id. Nr. DE 114 960 879

Tostedt HRB 3346 • GF: W. Ehrenholz