

## Technical Specification | Audience SUB-20A

|                              |                                  |                         |
|------------------------------|----------------------------------|-------------------------|
| Frequency response:          | 25 Hz - 150 Hz                   | ± 5 dB                  |
|                              | 32 Hz - 120 Hz                   | ± 3 dB                  |
| Crossover frequency:         | Variable low-pass:               | 60 Hz - 120 Hz          |
|                              | High-pass output:                | 80 Hz, 12 dB per octave |
| Sensitivity:                 | 50 mV                            |                         |
| Max. amplifier power output: | 90 W                             |                         |
| Max. SPL:                    | 101 dB (110 dB in a living room) |                         |
| Nominal impedance:           | Mono, left, right input          | 47 K ohms               |
| Driver:                      | 24 cm (10 inch)                  |                         |
| Dimensions (W x H x D):      | 276 x 430 x 455 mm               |                         |
| Weight:                      | 14 kg                            |                         |
| Power consumption:           | Standby                          | 10 W                    |
|                              | Max.                             | 150 W                   |

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)